

Serial No. 10/042,663
January 15, 2004
Reply to the Office Action dated October 15, 2003
Page 2 of 10

AMENDMENTS TO THE CLAIMS:

This listing of claims will replace all prior versions, and listings, of claims in the application:

LISTING OF CLAIMS:

Claim 1 (previously presented): A nonreciprocal circuit device comprising:
a permanent magnet;
a ferrite member which is arranged to receive a direct current magnetic field applied by the permanent magnet, said ferrite member including a plurality of central electrodes; and
a metal case containing the permanent magnet, the ferrite member, and the plurality of central electrodes;
wherein the metal case has a gap containing a solid insulating material for cutting off a loop current flowing around the ferrite member and the plurality of central electrodes.

Claim 2 (canceled).

Claim 3 (original): A nonreciprocal circuit device according to Claim 1, wherein the metal case is formed by a plurality of components.

Claim 4 (previously presented): A nonreciprocal circuit device according to Claim 1, wherein the metal case is 180° rotation-symmetric with respect to the axis of the permanent magnet.

Claim 5 (canceled).

Serial No. 10/042,663
January 15, 2004
Reply to the Office Action dated October 15, 2003
Page 3 of 10

Claim 6 (original): A nonreciprocal circuit device according to Claim 3, wherein the metal case is composed of an upper case unit and a lower case unit, and a gap is disposed at least between one edge of the upper case unit and one edge of the lower case unit opposite to the one edge of the upper case unit.

Claim 7 (original): A communication apparatus comprising at least one of the nonreciprocal circuit devices according to Claims 1 to 6.

Claim 8 (new): A nonreciprocal circuit device according to Claim 1, wherein the metal case is integrally formed.

Claim 9 (new): A nonreciprocal circuit device according to Claim 8, wherein a cross section of the metal case has a substantially rectangular frame shape formed by bending a substantially rectangular metal plate at four positions in parallel to an edge of the metal plate.